



OBJEKT	SLOUP	ÚROVEŇ KOTVENÍ [m]	ZATÍŽENÍ									
			STÁLÁ				NAHODILÁ					
			VL. TÍHA OK + ZAT. STÁLÉ				ÚŽITNÉ+SNĚH		VÍTR PŘÍČNÝ - X		VÍTR PODÉLNÝ - Y	
			Rx [kN]	Ry [kN]	Rz [kN]		Rx [kN]	Ry [kN]	Rz [kN]	Rx [kN]	Ry [kN]	Rz [kN]
A34 S	S93	-0.250	+5	400			250	±5	-20	±5	-20	
			navíc	110			90					
	S94	-0.250	+20	200		+5	100	±5	-70	±20	-10	
			navíc	55			45					
	S95	-0.250	±10	200		±5	50	±20	50	±20	-30	
			navíc	110			90					
	S96	-0.250	±20	150		±10	100	±20	-20		-30	
			navíc	110			90					
	S97	-0.250	±20	100		±5	50	±20	-10		-30	
			navíc	100			80					
	S98	-0.250		200			100	±5	-20		-40	
			navíc	165			135					
	S99	-0.250	±5	250			100	±5	-40		-60	
			navíc	220			180					
	S100	-0.250		100			50	±5	-10		-20	
			navíc	110			90					
	S110	-0.250		200			160					
	S111	-0.250		220			180					

TABULKA  
ZATĚŽOVACÍCH ÚDAJŮ

PÍSMENNÉ OSY (NAPŘ. A - X) - SMĚR xx  
ČÍSLOVANÉ OSY (NAPŘ. s41 - s56) - SMĚR yy

LEGENDA

 DOTČENÁ ČÁST OBJEKTU